



- Test E-vehicles during the charging process
- Data communication between EV and EVSE via fibre optic
- Low emission
- Supports all major standards:
CCS2, CHAdeMO, GB/T

FIBRE OPTIC CONVERTER FOR CAR CHARGING STATIONS

Certifications for the growing market of e-mobility require that the car (EV) is tested also while it is connected to the charging stations (EVSE) during the charging process.

The PONTIS EMC foCarCharger transmits the data signals via fibre optic connection. Due to the versatile concept of the converter it can be used with most international standards and be updated to new requirements.

The foCarCharger supports Pilot Signal (PWM), PLC and CAN communication. So multiple standards like CCS, CHAdeMO and GB/T are supported. Additionally it can read the relay contacts of CHAdeMO and other status signals.

The communication standard can easily be changed by switches on foCarCharger.

Both sides (EV and EVSE) are shielded and may be used inside the EMC chamber.

The firmware of the foCarCharger can be easily updated via a dedicated PC tool to react to future changes in the protocols.

As the EVSE needs to be separated from the EV, the power cables need to be separated from the data line. We offer a power connect box and corresponding charging cables.

FEATURES:

- Shielded transmission for car charging stations
- Data and power are split up
- Data transmission via fibre optics
- For AC and DC charging
- Most international standards supported
- RF-immunity 200 V/m up to 18 GHz
- Continuous operation with external 12V/2A power supply possible

ACCESSORIES:

required:

- Fibre optic cables: variable lengths ST/FSMA-connector (PONTIS EMC)

optional:

- Cable with appropriate connector for specific standard
- Power connect box (max. 230 A)

TECHNICAL DATA

Data communication	Control Pilot Circuit (PWM) PLC (HomePlug Green) up to 10 Mbps CAN bus (ISO11898) up to 1Mbps
Data link	Glass fibre 50/125 µm, ST connector
Operating temperature/humidity	0 ° to +50 °C / 20 to 80 % RH
Housing	coated aluminium
Colour	light grey (RAL 7035) / petrol
External dimensions	tbd
Weight	tbd
Immunity	200 V/m up to 18 GHz

Standards Supported



EC 61851-1 AC and DC CCS1 and 2 (PLC)



SAE J1772 AC and DC CCS1



GBT-18487.1 AC and DC



CHAdeMO DC

Specifications are subject to change without notice!

PONTIS
EMC PRODUCTS
A BRAND OF AUDIOVO

PONTIS EMC Products designed and manufactured by:

Audiovo GmbH
Irrenloher Damm 30
92521 Schwarzenfeld
Germany

Phone +49(9435) 54 19-0
Fax +49(9435) 54 19-19
info@audiovo.com
www.audiovo.com

You can contact directly our local partners for sales and technical support



www.hvtechnologies.com



india@pontis-emc.com



zongkui.shao@pontis-emc.com